



Hayat Kurtaran Bir Dokunuş!

DVC-CBL-101
DVC-RF-101

BEDSIDE CALL UNIT

TECHNICAL SPECIFICATIONS

	DVC-CBL-101	DVC-RF-101
Product Type	Wired	Wireless
El Seti	DVC-CBL-102	DVC-RF-102
Operating Voltage	12V DC	-
Alarm Current	<100mA	<100mA
Battery Requirement	-	12V / 23A
Operating Frequency	-	433MHz
Connection Type	CAT6	-
Operating Temperature	-10°C to +65°C	-10°C to +65°C
Casing	ABS	ABS
Protection Class	IP54	IP54



PRODUCT FEATURES

- Simple and aesthetic design suitable for any space
- Handset compatible
- Wired and wireless options
- Visual alert
- Maximum performance with powerful microprocessor
- Manual (button) call initiation and reset via device or handset
- Low power consumption in wireless versions
- Surface-mounted and flush-mounted options

ORDER

- DVC-CBL-101 Wired Bedside Call Unit (Flush Mount)
- DVC-CBL-101 Wired Bedside Call Unit (Surface Mount)
- DVC-RF-101 Wireless Bedside Call Unit (Flush Mount)
- DVC-RF-101 Wireless Bedside Call Unit (Surface Mount)

