



Hayat Kurtaran Bir Dokunuş!

DVC-CBL-103
DVC-RF-103

WC BATHROOM CALL UNIT

TECHNICAL SPECIFICATIONS



	DVC-CBL-103	DVC-RF-103
Product Type	Wired	Wireless
Operating Voltage	12V DC	-
Adapter Voltage	<100mA	<100mA
Battery Requirements	-	12V / 23A
Pull Cord	Was (140cm)	Was (140cm)
Operating Frequency	-	433MHz
Relay Type	Available	Available
Connection Type	CAT6	-
Operating Temperature	-10°C ile +65°C	-10°C to +65°C
Casing	ABS	ABS
Protection Class	IP54	IP54

PRODUCT FEATURES

- Simple and aesthetic design suitable for any space
- Wired and wireless options
- Visual alert
- Maximum performance with powerful microprocessor
- Low power consumption in wireless versions
- Call initiation with manual (button) or pull cord
- Surface-mounted and recessed options

ORDER

- DVC-CBL-103 Wired Toilet/Bathroom Call Unit (Flush Mount)
- DVC-CBL-103 Wired Toilet/Bathroom Call Unit (Surface Mounted)
- DVC-RF-103 Wireless Toilet/Bathroom Call Unit (Flush Mounted)
- DVC-RF-103 Wireless Toilet/Bathroom Call Unit (Surface Mounted)

